

WideTEK[®] 36 *Art*

The Art of Art Scanning

for all formats up to

914 x 1524 mm (36 x 60 inch)



**Contact free scanning at 600 dpi.
The art of art scanning!**



© 09_2017 / EN



- SCANS UP TO 914 X 1524 MM / 36 X 60 INCHES WIDE
- MAXIMUM SCAN HEIGHT OF 100 MM / 4 INCHES
- DOCUMENT THICKNESS OF 200 MM / 8 INCHES
- FASTEST COLOR SCANNING AT 42.2 MM/S / 1.66 INCH/S @ 300 DPI
- FASTEST 3D TEXTURE COLOR SCANNING AT 21.1 MM/S / 0.83 INCH/S @ 300DPI
- 600 x 600 DPI OPTICAL RESOLUTION
- CAPTURES 3D SURFACES, TEXTURES OF VARIOUS MATERIALS
- CONTACT-FREE SCANNING OF FRAGILE MATERIAL OR EVEN WET ARTWORK
- SCAN2PAD[®], USE ANY PAD TO OPERATE THE SCANNER
- SCAN TABLE CAN BE MOVED MANUALLY OR MOTORIZED
- INTEGRATED 64BIT LINUX, INTEL I3 QUAD CORE, 8 GB RAM, 320GB HDD
- GIGABIT TCP/IP NETWORK INTERFACE
- LARGE 15 INCH COLOR TOUCHSCREEN FOR SIMPLIFIED OPERATION
- VIRTUAL RESCAN, MODIFY IMAGES WITHOUT RESCANNING
- LED LAMPS, NO WARM UP, IR/UV FREE
- BUILT TO LAST
- EASY INSTALLATION VIA SCAN2NET[®] TECHNOLOGY



Enables contact free scanning of works of art like oil and acrylic paintings, watercolors, charcoal and pastel drawings, mixed media collages and antique works of art; at 600dpi in formats up to 914 x 1524mm / 36 x 60 inches.

Perfecting the Art of Art Scanning

WideTEK® 36ART

The WideTEK® 36 ART-600 enables contact free scanning of works of art like oil and acrylic paintings, watercolors, charcoal and pastel drawings, mixed media collages and antique works of art, with or without frames, gently and in high resolution.

With its patent pending laser focusing, the WideTEK 36 ART captures all surface textures, from the finest stroke of the brush to gouache painting techniques. Originals are scanned with up to 600 x 600 dpi optical resolution and ICC profiles can be easily used with the scanner to guarantee truly correct colors in the scanned image.

Contact free scanning allows a maximum height of the scanned surface of up to 100 mm and a complete height of the original of up to 200 mm. A framed work of art can be scanned directly without taking it out of the frame first.

The originals are moved under the CCD camera elements completely contact free, protecting works of art from any damage and making it possible to scan a painting that is still wet, as long as it is framed or the sides are dry enough to place the artwork on the scanning bed. Cool UV and IR-free LED illumination also protects valuable art from color distortion or damage due to excessive exposure to light.

In cooperation with large format printers from HP, Canon and EPSON, the WideTEK® 36 ART-600 brings the basis for professional art reproduction. Native printer drivers installed on the scanner make color accuracy on the resulting image even higher.

The WideTEK® 36 ART-600 was designed for archiving and reproduction of works of art. Museums can digitize their own collection for sale as a print or for publication on the internet or in catalogs. Reprography specialists can offer fine art digitization as a service, which has already proven to be a lucrative market.

WideTEK® 36ART Further highlights

- Output formats: PDF, PDF/A, JPEG, TIFF, PNM, multipage PDF and TIFF, DICOM and many more
- Authenticity of colors
- UV and IR-free LED lighting
- Geometrical accuracy
- Large color space: supports sRGB, Adobe RGB, native
- ICC color profile
- Scan2USB – Walk up scanning to a USB device
- Scan2Network – Output to network resources, SMB, FTP
- Virus resistant Linux – OS
- Remote maintenance and analysis
- Firmware updates via web interface

WideTEK® 36ART Markets

- Scanning artwork of all types and textures
- For museums, art dealers, auction houses, archives and libraries
- Scanning and texture recognition of surfaces for the industrial sector



WideTEK®36 ART-600 scans artwork up to 200 mm (8 inch) in thickness

Markets and Applications

The WideTEK® 36ART wide format CCD art scanner is a valuable production device for the following markets and applications. This list is neither complete

WideTEK® 36ART Markets

- Museums, Galleries, Exhibitions
- Copy Services, Reprographics
- Government, Archives, Special Collections
- Universities, Libraries, Fine Art Owners
- Textile, Floor Cover and Building material industries

nor exclusive, there are more markets and applications than listed and it should be taken only as a general guideline. If you have a specific application that is not listed here, please check with your sales representative.

WideTEK® 36ART Applications

- High quality replica production of artwork for sale in auction houses
- Preservation of artwork as special collections in museums
- Presentation of artwork in public and/or private catalogs, prints, websites
- Industrial quality control of textured heavy, thick or wet material

The Scan2Net® platform is the technological foundation of all WideTEK® and Bookeye® scanners from Image Access. It replaces the proprietary scanner drivers and software that traditional scanners require with the fastest common, nonproprietary inter-device connection available: TCP/IP over Ethernet. With network interface speeds much higher than USB 2.0 or USB 3.0 scanners, Scan2Net® devices are able to reach unrivaled performance at extremely low connectivity cost.

Scan2Net® scanners feature a 64bit Linux based operating system, dedicated to scanner specific imaging and mechanical control tasks, maximizing scanning speeds and performance.

Scan2Net® Advantages

- 64bit Linux based computer, fast and virus protected
- Easy integration into existing network structures
- Only a single IP address is required to run the scanner
- Integration and remote access via the Intranet or even the Internet
- Scans directly to SMB, FTP, hot folders, USB, Email or the Cloud without external PCs
- Simple, intuitive operation, Java and HTML based
- Clear menu structure, operation via touchscreen, acoustical feedback
- Multilanguage support, customizable user interface

TECHNICAL DATA

Maximum Document Size	914 x 1524 mm (36 x 60 inches)
Maximum Scan Heights	100 mm (4 inch)
Document Thickness	200 mm (8 inch) E.g. Canvas up to max. 100 mm in a frame up to 200 mm thickness
Optical Resolution	600 x 600 dpi
Scan Speed Color	300 dpi - 42.2 mm/s (1.66 inch/s), 600 dpi - 21.1 mm/s (0.83 inch/s)
Scan Speed Color 3D	300 dpi - 21.1 mm/s (0.83 inch/s), 600 dpi - 10.7 mm/s (0.42 inch/s)
Color Depth	48 bit color, 16 bit grayscale
Scan Output	24 bit color, 8 bit color indexed, 8 bit grayscale, bitonal, enhanced halftone
File Formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG), AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data
Camera	3x Tri-Color CCD, 67.500 pixels, encapsulated and dust-proof
Light Source	Two lamps with white LEDs, integrated optical diffusor, no IR/UV radiation
Computer	64 bit Linux, Intel i3, quad core processor, 8 Gigabyte RAM, 320GB HDD for extra large jobs
Touchscreen / Monitor	15 inch color touchscreen
USB Port	1 USB Port 3.0
Interface	1 GBit Fast Ethernet with TCP/IP based Scan2Net® Interface
Dimensions Scanner (H x W x D)	with runway: 1380 x 3275 x 1280 mm (54.3 x 128.9 x 50.4 inches) without runway: 1380 x 690 x 1280 mm (54.3 x 27.2 x 50.4 inches) Scan table: 1000 x 2100 mm (39.4 x 82.7 inches)
Weight Scanner	200 kg (440 lbs.)
Weight scan table	22,5 kg (50 lbs.)
Electrical Connection	100 – 240 Vac, 47 – 63 Hz (external power supply, complies with ECO standard CEC level VI)
Power Consumption	< 0.5 W (Sleep) / 5.2 W (Standby) / < 50 W (Ready to scan) / < 95 W (Scanning)
Operating Temperature	5 to 40 °C, 40 to 105 °F
Relative Humidity	20 to 80 % (non-condensing)
Noise	< 35 dB(A) (Scanning) / < 25 dB(A) (Standby)
Approvals	IEC/EN 62368-1: 2013, UL/CSA 62368-1 Ed.2, EN 55022, EN 55024; FCC 47 Part 15



WEEE



Visit our homepage!

IMAGE ACCESS GMBH

Hatzfelder Str. 161-163
42281 Wuppertal, Germany
Tel.: +49 (0)202 27058-0
www.imageaccess.de

IMAGE ACCESS LP

2511 Technology Drive, Suite 109
Elgin, IL 60124, USA
Office: +1 (224) 293-2585
Sales: +1 (727) 612-0809
www.imageaccess.us